CM710B Output Expansion Module

www.boschsecurity.com





The CM710B output expansion module allows quick and easy installation of addition physical outputs to the intrusion control panel. Being LAN based the CM710B may be co-located with the intrusion control panel or remotely located.

System overview

The CM710B Output expansion module is used to expand the number of outputs on the CC100 Solution 16i intrusion control panel.

Functions

Status LED

The module status LED flashes to indicate that the module is functioning correctly and communicating with the intrusion control panel. A steady LED indicates a communications failure.

Service code pad connection

Allows the temporary addition of a code pad locally to the module. This feature is especially useful for system maintenance of sites where the module is located away from the main control panel.

- ▶ 4 x Form C relay contacts
- LAN monitored
- Status LED
- Service code pad connection
- Separate tamper input

Separate tamper input

The separate tamper input allows installation of the module within its own secure enclosure without the need to utilise valuable intrusion inputs to provide cabinet tamper.

Installation/configuration notes

The CM710B is supplied as a PCB module and can be installed in the same cabinet as the main panel or remotely from the panel via the 4 wire LAN connection. The CM710B requires only one module space in the enclosure. Each module is given a separate module address selected via a three way dip switch.

Technical specifications

Power Requirements

Voltage	10.5 to 14 V D C
Current	30m A standby, 200m A MAX (all relays and LEDs operated)

Outputs	4 x Form C Relay outputs – contacts rated at 24VD C at 2A MAX
Cable	Max total LAN length using multi stranded security cable = 300m Max total LAN length using 2 pair twisted shielded data cable (Belden 8723) = 1500m

Environmental Considerations

Temperature	0 to 55 ° C
Humidity	5 % to 85 % at 30 ° C non condensing

Ordering information

CM710B Output Expansion Module

Order number CM710B

Represented by:

Americas:

Americas: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002

5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

© Bosch Security Systems 2013 | Data subject to change without notice 2856278155 | en, V1, 01. Oct 2013

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security Systems

11 Bishan Street 21 11 bisnan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2699 apr.securitysystems@bosch.com www.boschsecurity.asia

China:

China: Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.bacsbacurity.com.cn www.boschsecurity.com.cn

America Latina:

America Latina: Robert Bosch Ltda Security Systems Division Via Anhanguera, Km 98 CEP 13065-900 Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860 Fax: +55 19 2103 2862 Iatam.boschsecurity@bosch.com www.boschsecurity.com www.boschsecurity.com