RADION keyfob

www.boschsecurity.com





RADION wireless from Bosch provides the range, scalability and exceptional battery life required to ensure reliable performance and superior quality. Advanced diagnostics and multiple device enrollment options make installation and maintenance simple and cost effective. With a complete line of peripherals, RADION provides the flexibility for virtually any application requirement.

System overview

RADION keyfob allows you to arm or disarm the security system, or send a panic alarm. Programmed with a unique code, each model works exclusively with your compatible security system. On the four-button version, two option buttons are programmable to perform additional functions.

Functions

Panic alarm

The keyfob sends a panic code to your monitoring company if your security system is programmed to do so. Press both the lock and unlock buttons simultaneously for more than 600 milliseconds to send a panic alarm.



- Water and dust resistant
- Arm, disarm and panic functions
- Assigned by user for accurate reporting of open close signals
- LED indicator
- Programmable option buttons (only available on 4button model)

LED indicator

The LED flashes to indicate a signal was sent to your security system.

Programmable option buttons

The keyfob can be programmed to control additional devices in your protected area. Two option buttons are available.

Water and dust resistant

The housing is designed to resist dust and be resistant to water.

Encrypted transmission

RADION Keyfobs with synchronized encryption feature increased immunity to replay attacks, providing even more reliable system security.



Notice

Keyfobs with encryption require use of RADION receivers with firmware versions described in **Compatible Receivers** section

Certifications and approvals				
Region	Certi	Certificate		
US	ANSI/	UL 1023 – Household Burglar Alarm System Units ANSI/SIA CP-01-2010 (RFKF-FB-A/RFKF-TB-A/ RFKF-FBS-A/RFKF-TBS-A)		
Europe	Low-V Radio Termi EN50 EN50 Grade	CE EMC Directive (EMC) 2004/108/EC Low-Voltage Directive (LVD) 2006/95/EC Radio equipment and Telecommunications Terminal Equipment (R&TTE) 1999/5/EC EN50131-1 EN50131-3 EN50131-6 Grade 2 Environmental Class II		
Australia	RCM	RCM		
Region	Certific	Certification		
Australia	RCM	[RFKF-FB, RFKF-FBS, RFKF-TB, RFKF- TBS, RFPB-TB, RFPB-SB]		
Europe	CE	EMC, LVD, R&TTE, RoHS [RFKF-FB, RFKF-FBS, RFKF-TB, RFKF-TBS, RFPB- TB, RFPB-SB]		

EN-ST-000164 [RFKF-TB, RFKF-TBS]

EN-ST-000165 [RFKF-FB, RFKF-FBS]

Part 15 Security/Remote Control Trans-

mitter 433.42 MHZ [433.42 MHZ]

4349-13-1855 [RFKF-FB-A]

1249A-RWSSFT [-A model numbers]

4278-13-1855 [RFPB-SB-A; RFPB-TB-

Installation/configuration notes

ANATEL

ANATEL

EN5013

EN5013

1

1

FCC

IC

USA

Canada

Brazil

Recommended batteries

The following battery types are recommended for correct operation of your keyfob: Duracell DL2032, Varta CR2032, or Panasonic CR2032.

A; RFKF-TB-A]

Parts included

Quantity	Component
1	Keyfob
1	Lithium battery (CR2032) coin-cell, 3 VDC
1	Literature

Technical specifications

Properties

Dimensions	63.7 mm x 35.5 mm x 13.0 mm
	(2.51 in x 1.40 in x 0.51 in)

Power

Power/voltage	One CR2032 Lithium battery, 3 VDC		
Battery life	Up to 5 years		
Environmental considerations			
Temperature	Functional range: -10° C to $+49^{\circ}$ C (+14°F to +120°F) UL only: 0°C to +49°C (+32°F to+120°F) EN 50130-5 Class II only: -10° C to 40°C (+14°F to +104°F)		
Relative humidity	Up to 93% non-condensing		
Frequency	433.42 MHz		
Use	Intended for indoor use.		
Compatible receivers			
B810	SDI2 bus receiver		
RFRC-OPT	Option bus receiver		

i Notice

RFRC-STR

All RFKF-FBS/RFKF-TBS type keyfobs (including – A and –CHI versions) include synchronized encryption and are compatible only with RADION receivers having the following firmware versions or higher.

Streamline bus receiver

Compatible receiver	Receiver firmware version
B810	v2.01 or higher
RFRC-OPT	v1.3 or higher
RFRC-STR	v1.5 or higher

Trademarks

All hardware and software product names used in this document are likely to be registered trademarks and must be treated accordingly.

Ordering information

RFKF-FB (433.42 MHz)

Wireless, four-button key fob. For use in Europe, Africa, and Australia. Order number **RFKF-FB**

RFKF-FB-A (433.42 MHz)

Wireless, four-button key fob. For use in North and South America. Order number **RFKF-FB-A** **RFKF-FB-CHI (433.42 MHz)** Wireless, four-button key fob. For use in China only. Order number **RFKF-FB-CHI**

RFKF-FBS (433.42 MHz) Wireless, four-button key fob with encryption. For use in Europe, Africa, and Australia. Order number **RFKF-FBS**

RFKF-FBS-A (433.42 MHz)

Wireless, four-button key fob with encryption. For use in North and South America. Order number **BFKF-FBS-A**

RFKF-FBS-CHI (433.42 MHz)

Wireless, four-button key fob with encryption. For use in China only. Order number **RFKF-FBS-CHI**

RFKF-TB (433.42 MHz)

Wireless, two-button key fob. For use in Europe, Africa, and Australia. Order number **BFKF-TB**

RFKF-TB-A (433.42 MHz)

Wireless, two-button key fob. For use in North and South America. Order number **RFKF-TB-A**

RFKF-TB-CHI (433.42 MHz)

Wireless, two-button key fob. For use in China only. Order number **RFKF-TB-CHI**

RFKF-TBS (433.42 MHz)

Wireless, two-button key fob with encryption. For use in Europe, Africa, and Australia. Order number **RFKF-TBS**

RFKF-TBS-A (433.42 MHz)

Wireless, two-button key fob with encryption. For use in North and South America. Order number **RFKF-TBS-A**

RFKF-TBS-CHI (433.42 MHz)

Wireless, two-button key fob with encryption. For use in China only. Order number **RFKF-TBS-CHI**

Accessories

RADION beltclip

Belt clip for the RADION panic and keyfob transmitters. Includes clip-on attachment, 2 screws and secure locking nut, and comes in a 3-pack. Order number **RFAC-BC-3**

RADION lanyard

Necklace lanyard for the RADION panic and keyfob transmitters. 10 lanyards are individually packed in plastic bags. Order number **RFAC-LY-10**

Represented by:

Americas:

Americas: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa:

Europe, Middre East, Arrica: Bosch Security Systems B.V. P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security

Robert Bosch (SEA) Pto Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2699 apr.securitysystems@bosch.com www.boschsecurity.asia

North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.boschsecurity.com.cn

China:
America Latina:

Bosch (Shanghai) Security Systems Ltd.
Robert Bosch Ltda Security Systems Division

203 Building, No. 333 Fuquan Road
Via Anhanguera, Km 98

North IBP
CEP 13065-900

Changning District, Shanghai
Campinas, Sao Paulo, Brazil

200338 China
Phone: +55 19 2103 2860

Phone +86 21 22181111
Fax: +55 19 2103 2862

Crw. #66 21 321820
Interm Representation Representa latam.boschsecurity@bosch.com www.boschsecurity.com

© Bosch Security Systems 2016 | Data subject to change without notice 4296276491 | en, V20, 22. Jan 2016