

# EPA-NG/PLUS

## Electronic Hold Up Device

The EPA - NG is the most advanced Hold-Up device available on the market today. Packed with innovative features, this electronic unit is a versatile device capable of many functions.



- **Second Relay Output (for confirmed operation)**
- **One or Two Button Operation**
- **Timed Delay Operation**
- **LED Indicator**
- **Latching or Non Latching**
- **Selectable EOL Settings**
- **Keyless Reset**
- **PD6662:2010**

Connections	<b>10 PCB Terminals</b>	Temperature Range	<b>-15° C to +40° C</b>
Operation Method	<b>Single or Dual Push Button</b>	Tamper	<b>Cover</b>
Material	<b>ABS</b>	Reset Method	<b>Dual Push</b>
Dimensions mm	<b>85 x 85 x 39</b>	Colours	<b>White / Stainless Steel / Brass</b>
PA Output	<b>Programmable Latching / Non Latching Relay</b>	Confirmed Output	<b>N/C Relay</b>
Voltage Range	<b>12v DC</b>	Standards	<b>EN50131-1 Grade 3 / PD6662:2010 / BS8243:2010</b>
Current	<b>10mA @ 12Vdc</b>	Environmental Class	<b>II</b>
Output Option	<b>N/O or N/C Output / Instant or Delay Programmable</b>		